

SAFETY DATA SHEET 892-9001 KATKI MALZEMESİ (For Textured Paints)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 892-9001 KATKI MALZEMESİ (For Textured Paints)

Description Acrylic emulsion based additive material that recommended for textured paints.

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier

DYO Boya Fabrikaları San. ve Tic. A.Ş

D.O.S.B 2.Kısım Fırat Cad. No:11 Dilovası/Kocaeli/Turkey

www.dyo.com.tr 02627547560 02627547571

Contact person Kenan Sabak

Manufacturer

DYO Boya Fabrikaları San. ve Tic. A.Ş

D.O.S.B 2.Kısım Fırat Cad. No:11 Dilovası/Kocaeli/Turkey

www.dyo.com.tr 02627547560 02627547571

1.4. Emergency telephone number

Emergency telephone 02627547560 / 02624440396

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

2.2. Label elements

Hazard statements EUH208 Contains Mixture of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-

methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

Precautionary statements P102 Keep out of reach of children.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

892-9001 KATKI MALZEMESİ (For Textured Paints)

ETHANEDIOL 1-5%

CAS number: 107-21-1 EC number: 203-473-3

Classification

Acute Tox. 4 - H302

(Etilendioksi)dimetanol <1%

<1%

CAS number: 3586-55-8

Classification

Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Dam. 1 - H318

Mixture of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no.

247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-

239-6] (3:1)

CAS number: 55965-84-9

M factor (Acute) = 1 M factor (Chronic) = 1

Classification

Acute Tox. 3 - H301 Acute Tox. 3 - H311

Acute Tox. 3 - H331

Skin Corr. 1B - H314

Eye Dam. 1 - H318

Skin Sens. 1 - H317

Aquatic Acute 1 - H400

Aquatic Chronic 1 - H410

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information No special treatment required.

Inhalation Fresh air and rest.

Ingestion Rinse mouth. Give plenty of water to drink. Keep affected person under observation. Get

medical attention.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water.

Eye contact Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information See Section 11 for additional information on health hazards.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

892-9001 KATKI MALZEMESİ (For Textured Paints)

5.1. Extinguishing media

Suitable extinguishing media The product is non-combustible.

5.2. Special hazards arising from the substance or mixture

Specific hazards The product is not flammable.

5.3. Advice for firefighters

Protective actions during

No specific firefighting precautions known.

firefighting

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes and prolonged skin contact. Provide adequate ventilation. Wear

protective gloves.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with non-combustible, absorbent material. Flush contaminated area with

plenty of water. Contain spillage with sand, earth or other suitable non-combustible material.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health

hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Provide adequate ventilation.

Advice on general Wash hands and any other contaminated areas of the body with soap and water before

occupational hygiene leaving the work site.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store at moderate temperatures in dry, well ventilated area.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

ETHANEDIOL

Long-term exposure limit(TWA 8-hour): WEL 52 mg/m3(Sk) Short term exposure limit(STEL 15-minute): WEL 104 mg/m3(Sk)

Ingredient comments No exposure limits known for ingredient(s).

8.2. Exposure controls

892-9001 KATKI MALZEMESİ (For Textured Paints)

Protective equipment







Appropriate engineering

controls

Provide adequate ventilation.

Eye/face protection

Wear chemical splash goggles.

Hand protection

Wear protective gloves.

Other skin and body protection

Wear chemical protective suit.

Hygiene measures

Provide eyewash station. Remove contaminated clothing and wash the skin thoroughly with

soap and water after work.

Respiratory protection

No specific requirements are anticipated under normal conditions of use.

Environmental exposure

controls

Store in a demarcated bunded area to prevent release to drains and/or watercourses.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Liquid. Colour White

Odour Odourless.

Odour threshold Technically not feasible.

pН 8,0 - 9,0

Melting point Technically not feasible.

Initial boiling point and range Technically not feasible.

Flash point Technically not feasible.

Evaporation rate Technically not feasible.

Evaporation factor Technically not feasible.

Flammability (solid, gas) Technically not feasible.

Upper/lower flammability or

explosive limits

Technically not feasible.

Other flammability Technically not feasible.

Vapour pressure Technically not feasible.

Vapour density Technically not feasible.

Relative density No specific test data are available.

Bulk density 1,05 - 1,09 g/cm3, 25°C

Solubility(ies) Soluble in water.

Partition coefficient Technically not feasible. **Auto-ignition temperature** Technically not feasible.

892-9001 KATKI MALZEMESİ (For Textured Paints)

Decomposition Temperature No specific test data are available.

Explosive properties Technically not feasible.

Explosive under the influence

of a flame

Not considered to be explosive.

Oxidising properties There are no chemical groups present in the product that are associated with oxidising

properties.

Comments Information given is applicable to the product as supplied.

9.2. Other information

Refractive index Technically not feasible.

Particle size No specific test data are available.

Molecular weight Technically not feasible.

Volatility No specific test data are available.

Saturation concentration Technically not feasible.

Critical temperature Technically not feasible.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Will not polymerise.

10.4. Conditions to avoid

Conditions to avoid There are no known conditions that are likely to result in a hazardous situation.

10.5. Incompatible materials

Materials to avoid

No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Does not decompose when used and stored as recommended.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No information available.

Other health effects There is no evidence that the product can cause cancer.

General information No specific health hazards known.

Inhalation No specific health hazards known.

Skin contact No specific health hazards known.

892-9001 KATKI MALZEMESİ (For Textured Paints)

Eye contact May cause temporary eye irritation.

SECTION 12: Ecological Information

Ecotoxicity Not regarded as dangerous for the environment.

12.1. Toxicity

Toxicity The product is not believed to present a hazard due to its physical nature.

Acute toxicity - fish Not available.

Acute toxicity - aquatic

invertebrates

Not available.

Acute toxicity - aquatic plants Not available.

Acute toxicity -

Not available.

microorganisms

Acute toxicity - terrestrial Not available.

12.2. Persistence and degradability

Persistence and degradability The product is not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product is not bioaccumulating.

Partition coefficient Technically not feasible.

12.4. Mobility in soil

Mobility Not considered mobile.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects No information required.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority. Dispose of empty containers in accordance with national

regulations.

Disposal methods Burning

Waste class H-5

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

892-9001 KATKI MALZEMESİ (For Textured Paints)

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Dangerous Preparations Directive 1999/45/EC.

Dangerous Substances Directive 67/548/EEC.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

15.2. Chemical safety assessment

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

ATE: Acute Toxicity Estimate.

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service.
GHS: Globally Harmonized System.

LC₅o: Lethal Concentration to 50 % of a test population.

LD₅o: Lethal Dose to 50% of a test population (Median Lethal Dose).

ADR: European Agreement concerning the International Carriage of Dangerous Goods by

Road.

ADNR: European Agreement Concerning the International Carriage of Dangerous Goods by

Inland Waterways

RID: European Agreement concerning the International Carriage of Dangerous Goods by

Rail.

ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IMDG: International Maritime Dangerous Goods.

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation

(EC) No 1907/2006.

Revision comments This is first issue.

892-9001 KATKI MALZEMESİ (For Textured Paints)

Issued by Kenan Sabak / Dyo Architectural Paints Research and Development Specialsit.

Certified Safety Data Sheet Preparer, Certification no: GBF-1796

www.dyo.com.tr kenan.sabak@dyo.com.tr Tel: +90 262 754 75 60

Revision date 22/03/2017

Revision 0

Supersedes date 22/03/2017

SDS number 21047

Hazard statements in full H301 Toxic if swallowed.

H302 Harmful if swallowed. H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H331 Toxic if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH208 Contains Mixture of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

The information contained in this safety data sheet is provided in accordance with the requirements of the Chemicals (Hazard Information and Packaging) Regulations. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that requirements of relevant legislation are complied with. The information contained in this material safety data sheet is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.