



SAFETY DATA SHEET

266 DİNAMİK GRENLİ Exterior Textured Paint with Silicon

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 266 DİNAMİK GRENLİ Exterior Textured Paint with Silicon
Description Acrylic emulsion based, textured water borne matt exterior paint containing silicone additive.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses All types of interior and exterior mineral surfaces like masonry, concrete, plaster, brick, tile, asbestos, cement etc. It shouldn't be applied on the elastic paint systems.

1.3. Details of the supplier of the safety data sheet

Supplier DYO Boya Fabrikaları San. ve Tic. A.Ş.
D.O.S.B 2.Kısım Fırat Cad. No:11 Dilovası/Kocaeli/Turkey
www.dyo.com.tr
02627547560
02627547571

Manufacturer DYO Boya Fabrikaları San. ve Tic. A.Ş.
D.O.S.B 2.Kısım Fırat Cad. No:11 Dilovası/Kocaeli/Turkey
www.dyo.com.tr
02627547560
02627547571

1.4. Emergency telephone number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified
Health hazards Not Classified
Environmental hazards Not Classified

2.2. Label elements

Hazard statements EUH208 Contains 2-oktil-2H-izotiazol-3-on, karışım: 5-kloro-2-metil-4-izotiazolin-3-on [EC no. 247-500-7] ve 2-metil-2H-izotiazol-3-on [EC no. 220-239-6] (3:1). May produce an allergic reaction.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

266 DİNAMİK GRENLİ Exterior Textured Paint with Silicon

ETHANEDIOL	1-5%
CAS number: 107-21-1	EC number: 203-473-3
Classification	Classification (67/548/EEC or 1999/45/EC) Xn;R22
2-OCTYL-2H-ISOTHIAZOL-3-ONE	<1%
CAS number: 26530-20-1	EC number: 247-761-7
M factor (Acute) = 10	M factor (Chronic) = 1
Classification	Classification (67/548/EEC or 1999/45/EC) T;R23/24 C;R34 Xn;R22 R43 N;R50/53
Acute Tox. 3 - H331	
Skin Sens. 1 - H317	
Acute Tox. 3 - H311	
Eye Dam. 1 - H318	
Skin Corr. 1B - H314	
Aquatic Chronic 1 - H410	
Aquatic Acute 1 - H400	
Pyrithione Zinc	<1%
CAS number: 13463-41-7	EC number: 236-671-3
M factor (Acute) = 10	M factor (Chronic) = 1
Classification	Classification (67/548/EEC or 1999/45/EC) T; R23/25. Xi; R41. N; R50/53
Acute Tox. 3 - H301	
Acute Tox. 2 - H330	
Eye Dam. 1 - H318	
Aquatic Acute 1 - H400	
Aquatic Chronic 1 - H410	
DIURON (ISO)	<1%
CAS number: 330-54-1	EC number: 206-354-4
M factor (Acute) = 10	M factor (Chronic) = 10
Classification	Classification (67/548/EEC or 1999/45/EC) Carc. Cat. 3;R40 Xn;R22,R48/22 N;R50/53
Carc. 2 - H351	
STOT RE 2 - H373	
Aquatic Acute 1 - H400	
Aquatic Chronic 1 - H410	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Ingestion

Rinse mouth. Give plenty of water to drink. Keep affected person under observation. Get medical attention.

266 DİNAMİK GRENLİ Exterior Textured Paint with Silicon

Skin contact Remove contaminated clothing immediately and wash skin with soap and water.

Eye contact Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information See Section 11 for additional information on health hazards.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is non-combustible.

5.2. Special hazards arising from the substance or mixture

Specific hazards The product is not flammable.

5.3. Advice for firefighters

Protective actions during firefighting No specific firefighting precautions known.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes and prolonged skin contact. Provide adequate ventilation.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with non-combustible, absorbent material. Flush contaminated area with plenty of water. Contain spillage with sand, earth or other suitable non-combustible material.

6.4. Reference to other sections

Reference to other sections See Section 11 for additional information on health hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Provide adequate ventilation.

Advice on general occupational hygiene Wash hands and any other contaminated areas of the body with soap and water before leaving the work site.

7.2. Conditions for safe storage, including any incompatibilities

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

ETHANEDIOL

266 DİNAMİK GRENLİ Exterior Textured Paint with Silicon

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 104 mg/m³(Sk)

WEL = Workplace Exposure Limit

Ingredient comments No exposure limits known for ingredient(s).

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation.

Eye/face protection

Wear chemical splash goggles.

Other skin and body protection

Wear chemical protective suit.

Hygiene measures

Provide eyewash station. Remove contaminated clothing and wash the skin thoroughly with soap and water after work.

Respiratory protection

No specific requirements are anticipated under normal conditions of use.

Environmental exposure controls

Store in a demarcated bunded area to prevent release to drains and/or watercourses.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Odour	Odourless.
Odour threshold	Technically not feasible.
Melting point	Technically not feasible.
Initial boiling point and range	Technically not feasible.
Flash point	Technically not feasible.
Evaporation rate	Technically not feasible.
Evaporation factor	Technically not feasible.
Flammability (solid, gas)	Technically not feasible.
Upper/lower flammability or explosive limits	Technically not feasible.
Other flammability	Technically not feasible.
Vapour pressure	Technically not feasible.
Vapour density	Technically not feasible.
Relative density	No specific test data are available.
Bulk density	1,63 - 1,67 g/cm ³ , 25°C
Solubility(ies)	Soluble in water.

266 DİNAMİK GRENLI Exterior Textured Paint with Silicon

Partition coefficient	Technically not feasible.
Auto-ignition temperature	Technically not feasible.
Decomposition Temperature	No specific test data are available.
Viscosity	97-107 KU2/25°C
Explosive properties	Technically not feasible.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	There are no chemical groups present in the product that are associated with oxidising properties.
Comments	Information given is applicable to the product as supplied.

9.2. Other information

Refractive index	Technically not feasible.
Particle size	No specific test data are available.
Molecular weight	Technically not feasible.
Volatility	No specific test data are available.
Saturation concentration	Technically not feasible.
Critical temperature	Technically not feasible.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
-------------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures.
------------------	--

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid	There are no known conditions that are likely to result in a hazardous situation.
----------------------------	---

10.5. Incompatible materials

Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
---------------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	Does not decompose when used and stored as recommended.
---	---

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects	No information available.
Other health effects	There is no evidence that the product can cause cancer.
Acute toxicity - oral	
ATE oral (mg/kg)	200,000.0

266 DİNAMİK GRENLİ Exterior Textured Paint with Silicon

Eye contact May cause temporary eye irritation.

SECTION 12: Ecological Information

Ecotoxicity Not regarded as dangerous for the environment.

12.1. Toxicity

Acute toxicity - fish Not available.

Acute toxicity - aquatic invertebrates Not available.

Acute toxicity - aquatic plants Not available.

Acute toxicity - microorganisms Not available.

Acute toxicity - terrestrial Not available.

12.2. Persistence and degradability

Persistence and degradability The product is not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product is not bioaccumulating.

Partition coefficient Technically not feasible.

12.4. Mobility in soil

Mobility Not considered mobile.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects No information required.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

266 DİNAMİK GRENLİ Exterior Textured Paint with Silicon

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Dangerous Preparations Directive 1999/45/EC.
 Dangerous Substances Directive 67/548/EEC.
 Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
 Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Water hazard classification N/A

15.2. Chemical safety assessment

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

ATE: Acute Toxicity Estimate.

CAS: Chemical Abstracts Service.

GHS: Globally Harmonized System.

LC₅₀: Lethal Concentration to 50 % of a test population.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.

ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IMDG: International Maritime Dangerous Goods.

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.

Revision date 18/05/2016

Revision 0.1

Supersedes date 18/05/2016

SDS number 20771

Risk phrases in full R48/22 Harmful: danger of serious damage to health by prolonged exposure if swallowed.

266 DİNAMİK GRENLİ Exterior Textured Paint with Silicon

Hazard statements in full

H301 Toxic if swallowed.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H330 Fatal if inhaled.
H331 Toxic if inhaled.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
EUH208 Contains 2-OCTYL-2H-ISOTHIAZOL-3-ONE, Mixture of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.