

SAFETY DATA SHEET 328 DYOFLEKS Water Proofing Sealer For Roofs

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 328 DYOFLEKS Water Proofing Sealer For Roofs

Description Acrylic emulsion based, water proofing sealer for roofs.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Exterior masonry, concrete, plaster, ytong, brick, fiber cement, wood, roof boarding plates,

roofs and terraces.

1.3. Details of the supplier of the safety data sheet

Supplier DYO Boya Fabrikaları San. ve Tic. A.Ş

D.O.S.B 2.Kısım Fırat Cad. No:11 Dilovası/Kocaeli/Turkey

www.dyo.com.tr 02627547560 02627547571

Contact person Kenan Sabak

Manufacturer DYO Boya Fabrikaları San. ve Tic. A.Ş

D.O.S.B 2.Kısım Fırat Cad. No:11 Dilovası/Kocaeli/Turkey

www.dyo.com.tr 02627547560 02627547571

1.4. Emergency telephone number

Emergency telephone 02627547560 / 02624440396

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC/1272/2008)

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

2.2. Label elements

Hazard statements EUH208 Contains 2-OCTYL-2H-ISOTHIAZOL-3-ONE, Mixture of 5-chloro-2-methyl-4-

isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6]

(3:1). May produce an allergic reaction.

Precautionary statements P102 Keep out of reach of children.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

328 DYOFLEKS Water Proofing Sealer For Roofs

 ETHANEDIOL
 1-5%

 CAS number: 107-21-1
 EC number: 203-473-3

Classification Classification (67/548/EEC or 1999/45/EC)

Acute Tox. 4 - H302 Xn;R22

2-OCTYL-2H-ISOTHIAZOL-3-ONE <1%

 Classification
 Classification (67/548/EEC or 1999/45/EC)

 Acute Tox. 4 - H302
 T;R23/24 C;R34 Xn;R22 R43 N;R50/53

Acute Tox. 3 - H311 Acute Tox. 3 - H331 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

Pyrithione Zinc <1%

Classification Classification (67/548/EEC or 1999/45/EC)

Acute Tox. 3 - H301 Acute Tox. 2 - H330 Eye Dam. 1 - H318 Aquatic Acute 1 - H400

Aquatic Chronic 1 - H410

DIURON (ISO) <1%

Classification (67/548/EEC or 1999/45/EC)

Acute Tox. 4 - H302 Carc. 2 - H351 STOT RE 2 - H373 Aquatic Acute 1 - H400

Aquatic Chronic 1 - H410

Carc. Cat. 3;R40 Xn;R22,R48/22 N;R50/53

T; R23/25. Xi; R41. N; R50/53

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information No special treatment required.

Inhalation Fresh air and rest.

328 DYOFLEKS Water Proofing Sealer For Roofs

Ingestion Rinse mouth. Give plenty of water to drink. Keep affected person under observation.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water.

Eye contact Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information No special treatment required.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is non-combustible.

5.2. Special hazards arising from the substance or mixture

Specific hazards The product is not flammable.

5.3. Advice for firefighters

Protective actions during

firefighting

No specific firefighting precautions known.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes and prolonged skin contact. Provide adequate ventilation. Wear

protective gloves.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Absorb spillage with non-combustible, absorbent material. Flush contaminated area with

plenty of water. Contain spillage with sand, earth or other suitable non-combustible material.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health

hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Provide adequate ventilation.

Advice on general Wash hands and any other contaminated areas of the body with soap and water before

occupational hygiene leaving the work site.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store at moderate temperatures in dry, well ventilated area.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

328 DYOFLEKS Water Proofing Sealer For Roofs

Occupational exposure limits

ETHANEDIOL

Long-term exposure limit(TWA 8-hour): WEL 52 mg/m3(Sk) Short term exposure limit(STEL 15-minute): WEL 104 mg/m3(Sk)

Ingredient comments No exposure limits known for ingredient(s).

8.2. Exposure controls

Protective equipment







Appropriate engineering

controls

Provide adequate ventilation.

Eye/face protection Wear chemical splash goggles.

Hand protection Wear protective gloves.

Other skin and body

protection

Wear chemical protective suit.

Hygiene measures Provide eyewash station. Remove contaminated clothing and wash the skin thoroughly with

soap and water after work.

Respiratory protection No specific requirements are anticipated under normal conditions of use.

Environmental exposure

controls

Store in a demarcated bunded area to prevent release to drains and/or watercourses.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.

Colour Various colours.

Odourless.

Odour threshold Technically not feasible.

pH 8,0 - 8,4

Melting point Technically not feasible.

Initial boiling point and range Technically not feasible.

Flash point Technically not feasible.

Evaporation rate Technically not feasible.

Evaporation factor Technically not feasible.

Flammability (solid, gas) Technically not feasible.

Upper/lower flammability or

explosive limits

Technically not feasible.

Other flammability Technically not feasible.

Vapour pressure Technically not feasible.

Vapour density Technically not feasible.

328 DYOFLEKS Water Proofing Sealer For Roofs

Relative density No specific test data are available.

Bulk density 1,34 - 1,38 g/cm3, 25°C'de

Solubility(ies) Soluble in water.

Partition coefficient Technically not feasible.

Auto-ignition temperature Technically not feasible.

Decomposition Temperature No specific test data are available.

Viscosity 107-113 KU1/25°C

Explosive properties Technically not feasible.

Explosive under the influence

of a flame

Not considered to be explosive.

Oxidising properties There are no chemical groups present in the product that are associated with oxidising

properties.

Comments Information given is applicable to the product as supplied.

9.2. Other information

Refractive index Technically not feasible.

Particle size No specific test data are available.

Molecular weight Technically not feasible.

Volatility No specific test data are available.

Saturation concentration Technically not feasible.

Critical temperature Technically not feasible.

Volatile organic compound <40 g/L (Theoretical), Directive 2004/42/CE Annex II.A-c

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Will not polymerise.

10.4. Conditions to avoid

Conditions to avoid There are no known conditions that are likely to result in a hazardous situation.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Does not decompose when used and stored as recommended.

328 DYOFLEKS Water Proofing Sealer For Roofs

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Other health effects There is no evidence that the product can cause cancer.

.

General information No specific health hazards known.

Inhalation No specific health hazards known.

Ingestion Harmful if swallowed.

Skin contact No specific health hazards known.

Eye contact May cause temporary eye irritation.

Route of entry Ingestion.

SECTION 12: Ecological Information

Ecotoxicity Not regarded as dangerous for the environment.

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability The product is not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product is not bioaccumulating.

Partition coefficient Technically not feasible.

12.4. Mobility in soil

Mobility Not considered mobile.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects No information required.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority. Dispose of empty containers in accordance with national regulations. International Disposal Code of product: 080111 International Disposal code of

containers: 150110

Disposal methods Burning
Waste class H-5

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

14.1. UN number

328 DYOFLEKS Water Proofing Sealer For Roofs

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

Nο

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Dangerous Preparations Directive 1999/45/EC.

Dangerous Substances Directive 67/548/EEC.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH)(as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

15.2. Chemical safety assessment

SECTION 16: Other information

Abbreviations and acronyms

ATE: Acute Toxicity Estimate.

used in the safety data sheet ADR: European Agreement concerning the International Carriage of Dangerous Goods by

Road.

ADN: European Agreement concerning the International Carriage of Dangerous Goods by

Inland Waterways.

CAS: Chemical Abstracts Service.

DNEL: Derived No Effect Level.

GHS: Globally Harmonized System.

IATA: International Air Transport Association.

ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IMDG: International Maritime Dangerous Goods.

LC₅o: Lethal Concentration to 50 % of a test population.

LD₅o: Lethal Dose to 50% of a test population (Median Lethal Dose).

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation

(EC) No 1907/2006.

RID: European Agreement concerning the International Carriage of Dangerous Goods by

Rail.

328 DYOFLEKS Water Proofing Sealer For Roofs

General information The temperature of the surface should not be lower than 5°C.

Revision comments This is first issue.

Issued by Kenan Sabak / Dyo Architectural Paints Research and Development Specialsit.

Certified Safety Data Sheet Preparer, Certification no: GBF-1796

www.dyo.com.tr kenan.sabak@dyo.com.tr Tel: +90 262 754 75 60

Revision date 01/06/2016

Revision 0.1

Supersedes date 01/06/2016

SDS number 20805

Hazard statements in full H301 Toxic if swallowed.

H302 Harmful if swallowed. H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H330 Fatal if inhaled. H331 Toxic if inhaled.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH208 Contains 2-OCTYL-2H-ISOTHIAZOL-3-ONE, Mixture of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6]

(3:1). May produce an allergic reaction.

The information contained in this safety data sheet is provided in accordance with the requirements of the Chemicals (Hazard Information and Packaging) Regulations. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that requirements of relevant legislation are complied with. The information contained in this material safety data sheet is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.