



## SAFETY DATA SHEET

### 981- PINOSAN Wood Varnish

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

**Product name** 981- PINOSAN Wood Varnish

**Description** Alkyd based solvent-borne, transparent, semi matt decorative wood varnish.

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Suitable for all kinds of wood used for interior and exterior joinery, wood siding, wood garden furniture, ready-coated plate surfaces looks like wood and also for panels.

##### 1.3. Details of the supplier of the safety data sheet

**Supplier** DYO Boya Fabrikaları San. ve Tic. A.Ş  
D.O.S.B 2.Kısım Fırat Cad. No:11 Dilovası/Kocaeli/Turkey  
02627547560  
02627547571  
www.dyo.com.tr

**Contact person** Olcay EREN

**Manufacturer** DYO Boya Fabrikaları San.ve Tic. A.Ş  
Atatürk Organize Sanayi Bölgesi 10003 Sok. No:2 35620 Çiğli/İzmir/Turkey  
02323280880  
02323768055  
www.dyo.com.tr

##### 1.4. Emergency telephone number

**Emergency telephone** 02627547560 / 02624440396 02323280880

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)

**Physical hazards** Flam. Liq. 3 - H226

**Health hazards** Skin Sens. 1 - H317 STOT SE 3 - H336 Asp. Tox. 1 - H304

**Environmental hazards** Aquatic Chronic 2 - H411

##### 2.2. Label elements

###### Hazard pictograms



**Signal word**

Danger

## 981- PINOSAN Wood Varnish

### Hazard statements

H226 Flammable liquid and vapour.  
 H304 May be fatal if swallowed and enters airways.  
 H317 May cause an allergic skin reaction.  
 H336 May cause drowsiness or dizziness.  
 H411 Toxic to aquatic life with long lasting effects.

### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P240 Ground and bond container and receiving equipment.  
 P241 Use explosion-proof electrical equipment.  
 P242 Use non-sparking tools.  
 P243 Take action to prevent static discharges.  
 P261 Avoid breathing vapour/ spray.  
 P271 Use only outdoors or in a well-ventilated area.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
 P302+P352 IF ON SKIN: Wash with plenty of water.  
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P312 Call a POISON CENTRE/doctor if you feel unwell.  
 P321 Specific treatment (see medical advice on this label).  
 P331 Do NOT induce vomiting.  
 P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.  
 P362+P364 Take off contaminated clothing and wash it before reuse.  
 P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.  
 P391 Collect spillage.  
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
 P403+P235 Store in a well-ventilated place. Keep cool.  
 P405 Store locked up.  
 P501 İçeriği/kabı Çevre ve Şehircilik Bakanlığı'nın "Atık Yönetimi Yönetmeliği" Madde 9'a göre bertaraf edin.

### Contains

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), 2-bütanonoksim, 3-iodo2-propynyl butyl carbamate, cobalt bis(2-ethylhexanoate)

### 2.3. Other hazards

#### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	<b>40-60%</b>
--	---------------

CAS number: 64742-82-1

EC number: 919-446-0

REACH registration number: 01-  
2119458049-33-0007

#### Classification

Flam. Liq. 3 - H226

STOT SE 3 - H336

Asp. Tox. 1 - H304

Aquatic Chronic 2 - H411

## 981- PINOSAN Wood Varnish

<b>2-bütanonoksim</b>	<b>&lt;0,7%</b>
CAS number: 96-29-7	EC number: 202-496-6
<b>Classification</b>	
Acute Tox. 4 - H312	
Eye Dam. 1 - H318	
Skin Sens. 1 - H317	
Carc. 2 - H351	
<b>3-iodo2-propynyl butyl carbamate</b>	<b>0,3±0,03%</b>
CAS number: 55406-53-6	EC number: 259-627-5
M factor (Acute) = 10	M factor (Chronic) = 1
<b>Classification</b>	
Acute Tox. 4 - H302	
Acute Tox. 3 - H331	
Eye Dam. 1 - H318	
Skin Sens. 1 - H317	
STOT RE 1 - H372	
Aquatic Acute 1 - H400	
Aquatic Chronic 1 - H410	
<b>cobalt bis(2-ethylhexanoate)</b>	<b>&lt;0,2%</b>
CAS number: 136-52-7	EC number: 205-250-6
M factor (Acute) = 1	
<b>Classification</b>	
Eye Irrit. 2 - H319	
Skin Sens. 1A - H317	
Repr. 2 - H361	
Aquatic Acute 1 - H400	
Aquatic Chronic 3 - H412	

The full text for all hazard statements is displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	Get medical attention if any discomfort continues.
<b>Inhalation</b>	Remove person to fresh air and keep comfortable for breathing. If breathing stops, provide artificial respiration. Get medical attention if any discomfort continues.
<b>Ingestion</b>	Do not induce vomiting. Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable seek hospital and bring these instructions.
<b>Skin contact</b>	Kirlenmiş giysileri hemen çıkarıp, deriyi su ve sabunla yıkayın. Get medical attention if irritation persists after washing. Show this Safety Data Sheet to the medical personnel.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Get medical attention if any discomfort continues.
<b>Protection of first aiders</b>	No specific requirements are anticipated under normal conditions of use.

## 981- PINOSAN Wood Varnish

### 4.2. Most important symptoms and effects, both acute and delayed

**General information** Not dangerous under normal conditions. Get medical attention if any discomfort continues, and take this SDS with you.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes for the doctor** Semptomlara göre tedavi ediniz.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**Suitable extinguishing media** Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m<sup>3</sup>. Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours.

### 5.3. Advice for firefighters

**Protective actions during firefighting** Avoid breathing fire gases or vapours. Risk of re-ignition after fire has been extinguished. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapours. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Use special protective clothing. Regular protection may not be safe. Cool containers exposed to flames with water until well after the fire is out. Containers close to fire should be removed or cooled with water. Do not allow water to contact any leaked material. Control run-off water by containing and keeping it out of sewers and watercourses.

**Special protective equipment for firefighters** Wear chemical protective suit. Use air-supplied respirator, gloves and protective goggles. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Wear protective clothing as described in Section 8 of this safety data sheet. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Take precautionary measures against static discharges. Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation.

### 6.2. Environmental precautions

**Environmental precautions** Do not discharge into drains or watercourses or onto the ground. Avoid release to the environment. Collect and dispose of spillage as indicated in Section 13.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Avoid contact with skin or inhalation of spillage, dust or vapour. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13. Flush contaminated area with plenty of water. Take care as floors and other surfaces may become slippery.

### 6.4. Reference to other sections

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

## 981- PINOSAN Wood Varnish

**Usage precautions** Do not eat, drink or smoke when using the product. Avoid inhalation of vapours/spray and contact with skin and eyes. Provide adequate ventilation. Persons with impaired lung function should not handle this product..

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Keep separate from food, feedstuffs, fertilisers and other sensitive material. Avoid contact with oxidising agents. Take precautionary measures against static discharges. Store in tightly-closed, original container in a well-ventilated place. Store between 5 and 25°C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Containers, which are opened should be properly resealed and kept upright to prevent leakage.

**Storage class** Chemical storage.

### 7.3. Specific end use(s)

## SECTION 8: Exposure controls/Personal protection

### 8.1. Control parameters

### 8.2. Exposure controls

#### Protective equipment



**Appropriate engineering controls** Provide adequate ventilation. Avoid inhalation of vapours.

**Eye/face protection** Wear tight-fitting, chemical splash goggles or face shield.

**Hand protection** Use protective gloves.

**Other skin and body protection** Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

**Hygiene measures** Provide eyewash station. Wash promptly if skin becomes contaminated. Contaminated clothing should be placed in a closed container for disposal or decontamination. Warn cleaning personnel of any hazardous properties of the product. Remove contaminated clothing and wash the skin thoroughly with soap and water after work. When using do not eat, drink or smoke.

**Respiratory protection** If ventilation is inadequate, suitable respiratory protection must be worn.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Liquid.
<b>Colour</b>	Clear
<b>Odour</b>	Solvent.
<b>Odour threshold</b>	No information required.
<b>pH</b>	Technically not feasible.
<b>Melting point</b>	Technically not feasible.
<b>Initial boiling point and range</b>	140 - 220 °C
<b>Flash point</b>	38°C Closed cup.

## 981- PINOSAN Wood Varnish

<b>Evaporation rate</b>	No specific test data are available.
<b>Evaporation factor</b>	No specific test data are available.
<b>Flammability (solid, gas)</b>	No specific test data are available.
<b>Upper/lower flammability or explosive limits</b>	LEL : 0,21% volume / UEL : 2,8% volume
<b>Other flammability</b>	No specific test data are available.
<b>Vapour pressure</b>	<200 mmHg at 38°C
<b>Vapour density</b>	No specific test data are available.
<b>Relative density</b>	Technically not feasible.
<b>Bulk density</b>	0,90 - 0,94 g/cm <sup>3</sup> , 25°C'de
<b>Solubility(ies)</b>	Insoluble in water.
<b>Partition coefficient</b>	No specific test data are available.
<b>Auto-ignition temperature</b>	No specific test data are available.
<b>Decomposition Temperature</b>	Technically not feasible.
<b>Viscosity</b>	28 - 34 s/D4, 25°C'de
<b>Explosive properties</b>	Technically not feasible.
<b>Explosive under the influence of a flame</b>	Not considered to be explosive.
<b>Oxidising properties</b>	There are no chemical groups present in the product that are associated with oxidising properties.
<b>Comments</b>	Information given is applicable to the product as supplied.

### 9.2. Other information

**Volatile organic compound** < 460 g/L (Theoretical) Directive 2004/42/CE Annex II.A-e

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity** Keep away from oxidizing agents, strongly alkaline and acidic materials to prevent the possibility of exothermic reaction.

### 10.2. Chemical stability

**Stability** Stable at normal ambient temperatures and when used as recommended.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** Will not polymerise.

### 10.4. Conditions to avoid

**Conditions to avoid** Avoid contact with strong oxidising agents. Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or direct sunlight.

### 10.5. Incompatible materials

**Materials to avoid** Strong alkalis. Strong acids.

### 10.6. Hazardous decomposition products

## 981- PINOSAN Wood Varnish

**Hazardous decomposition products** Carbon monoxide (CO). Oxides of carbon. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m<sup>3</sup>.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

**Toxicological effects** No information available.

**Other health effects** There is no evidence that the product can cause cancer.

#### Skin corrosion/irritation

**Skin corrosion/irritation** Repeated exposure may cause skin dryness or cracking.

#### Serious eye damage/irritation

**Serious eye damage/irritation** Repeated exposure may cause chronic eye irritation.

#### Respiratory sensitisation

**Respiratory sensitisation** Vapour from this chemical can be hazardous when inhaled. Gas or vapour at high concentrations may irritate respiratory system.

#### Skin sensitisation

**Skin sensitisation** Repeated exposure may cause skin dryness or cracking.

#### Specific target organ toxicity - single exposure

**STOT - single exposure** May cause drowsiness or dizziness.

**Target organs** Central nervous system

#### Aspiration hazard

**Aspiration hazard** May be fatal if swallowed and enters airways.

**Toxicological classifications are based on available information. RTECS (Portland Cement): VV8770000**

#### Toxicological information on ingredients.

##### 2-bütanonoksim

#### Acute toxicity - dermal

**ATE dermal (mg/kg)** 1,100.0

##### 3-iodo2-propynyl butyl carbamate

#### Acute toxicity - oral

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 1,400.0

**Species** Rat

**ATE oral (mg/kg)** 1,400.0

#### Acute toxicity - dermal

**Acute toxicity dermal (LD<sub>50</sub> mg/kg)** 2,100.0

**Species** Rabbit

## 981- PINOSAN Wood Varnish

ATE dermal (mg/kg)	2,100.0
<u>Acute toxicity - inhalation</u>	
Acute toxicity inhalation (LC <sub>50</sub> vapours mg/l)	2.756
Species	Rat
ATE inhalation (vapours mg/l)	2.756

### SECTION 12: Ecological information

#### 12.1. Toxicity

##### Acute aquatic toxicity

Acute toxicity - fish LC<sub>50</sub>, 96 hours: Veri yok mg/l, Fish

Acute toxicity - aquatic invertebrates EC<sub>50</sub>, 48 hours: Veri yok. mg/l, Daphnia magna

Acute toxicity - aquatic plants IC<sub>50</sub>, 72 hours: Veri yok. mg/l, Algae

##### Ecological information on ingredients.

##### 3-iodo2-propynyl butyl carbamate

##### Acute aquatic toxicity

LE(C)<sub>50</sub> 0.01 < L(E)C50 ≤ 0.1

M factor (Acute) 10

##### Chronic aquatic toxicity

M factor (Chronic) 1

##### cobalt bis(2-ethylhexanoate)

##### Acute aquatic toxicity

LE(C)<sub>50</sub> 0.1 < L(E)C50 ≤ 1

M factor (Acute) 1

#### 12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

#### 12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient No specific test data are available.

#### 12.4. Mobility in soil

Mobility The product contains substances which are insoluble in water and which may spread on water surfaces.

#### 12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

#### 12.6. Other adverse effects

### SECTION 13: Disposal considerations



## 981- PINOSAN Wood Varnish

### 13.1. Waste treatment methods

<b>General information</b>	When handling waste, the safety precautions applying to handling of the product should be considered. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Dispose of empty containers in accordance with national regulations. International Disposal Code of product : 080111 International Disposal code of containers : 150110
<b>Disposal methods</b>	Burning
<b>Waste class</b>	H3-B H-5

### SECTION 14: Transport information

#### 14.1. UN number

UN No. (ADR/RID)	1263
UN No. (IMDG)	1263
UN No. (ICAO)	1263
UN No. (ADN)	1263

#### 14.2. UN proper shipping name

Proper shipping name (ADR/RID) PAINT

Proper shipping name (IMDG) PAINT (CONTAINS cobalt bis(2-ethylhexanoate), hidrokarbonlar, C9-C12, n-alkanlar, iso alkanlar, siklik bileşimler, aromalar (2-25%))

Proper shipping name (ICAO) PAINT

Proper shipping name (ADN) PAINT

#### 14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3

#### Transport labels



#### 14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ICAO packing group	III
ADN packing group	III

#### 14.5. Environmental hazards

## 981- PINOSAN Wood Varnish

Environmentally hazardous substance/marine pollutant



### 14.6. Special precautions for user

EmS	F-E, S-E
ADR transport category	3
Emergency Action Code	•3Y
Hazard Identification Number (ADR/RID)	30
Tunnel restriction code	(D/E)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation	Dangerous Preparations Directive 1999/45/EC. Dangerous Substances Directive 67/548/EEC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)(as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
----------------	---

### 15.2. Chemical safety assessment

## SECTION 16: Other information

Revision comments	Product name change.
Issued by	OLCAY EREN/ DYO İnşaat Boyaları Ar-Ge Mühendisi Sertifikalı Güvenlik Bilgi Formu Hazırlayıcısı, Sertifika no: GBF-A-0-2883 www.dyo.com.tr olcay.eren@dyo.com.tr Tel : +90 262 754 75 60
Revision date	01/06/2020
Revision	0.3
Supersedes date	27/01/2016
SDS number	20448

## 981- PINOSAN Wood Varnish

### Hazard statements in full

H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H331 Toxic if inhaled.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer.  
H361 Suspected of damaging fertility or the unborn child if swallowed.  
H372 Causes damage to organs (Larynx) through prolonged or repeated exposure.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.