



SAFETY DATA SHEET

987- MASSIVELINE Teak Oil

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 987- MASSIVELINE Teak Oil

Description It's a special product developed for an easy and quick maintenance of outdoor wooden surfaces and hardwoods like teak, mahogany and rosewood.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses All types of wood exposed outside especially incontact with water such as flooring, swimming pool borders, decks and also for garden furniture.

1.3. Details of the supplier of the safety data sheet

Supplier DYO Boya Fabrikaları San. ve Tic. A.Ş
D.O.S.B 2.Kısım Fırat Cad. No:11 Dilovası/Kocaeli/Turkey
www.dyo.com.tr
02627547560
02627547571

Contact person Elvan Sağlam

Manufacturer DYO Boya Fabrikaları San.ve Tic. A.Ş
Atatürk Organize Sanayi Bölgesi 10003 Sok. No:2 35620 Çiğli/İzmir/Turkey
02323280880
02323768055
www.dyo.com.tr

1.4. Emergency telephone number

Emergency telephone 02627547560 / 02624440396 02323280880

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC/1272/2008)

Physical hazards Flam. Liq. 3 - H226

Health hazards STOT SE 3 - H336 Asp. Tox. 1 - H304

Environmental hazards Aquatic Chronic 2 - H411

2.2. Label elements

Pictogram



Signal word

Danger

987- MASSIVELINE Teak Oil

Hazard statements	<p>H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. EUH208 Contains 2-bütanonoksim, 3-iodo2-propynyl butyl carbamate, cobalt bis(2-ethylhexanoate). May produce an allergic reaction.</p>
Precautionary statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 Ground/ bond container and receiving equipment. P241 Use explosion-proof electrical equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing vapour/ spray. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/ doctor if you feel unwell. P331 Do NOT induce vomiting. P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish. P391 Collect spillage. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. P501 İçeriği/kabı Çevre ve Şehircilik Bakanlığı'nın "Atık Yönetimi Yönetmeliği" Madde 9'a göre bertaraf edin.</p>
Contains	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	60-80%
CAS number: 64742-82-1	EC number: 919-446-0
	REACH registration number: 01-2119458049-33-0007
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	

987- MASSIVELINE Teak Oil

2-bütanonoksim	<0,4%
CAS number: 96-29-7	EC number: 202-496-6
Classification	
Acute Tox. 4 - H312	
Eye Dam. 1 - H318	
Skin Sens. 1 - H317	
Carc. 2 - H351	
3-iodo2-propynyl butyl carbamate	0,1±0,01%
CAS number: 55406-53-6	EC number: 259-627-5
M factor (Acute) = 10	M factor (Chronic) = 1
Classification	
Acute Tox. 4 - H302	
Acute Tox. 3 - H331	
Eye Dam. 1 - H318	
Skin Sens. 1 - H317	
STOT RE 1 - H372	
Aquatic Acute 1 - H400	
Aquatic Chronic 1 - H410	
cobalt bis(2-ethylhexanoate)	<0,1%
CAS number: 136-52-7	EC number: 205-250-6
M factor (Acute) = 1	
Classification	
Eye Irrit. 2 - H319	
Skin Sens. 1A - H317	
Repr. 2 - H361	
Aquatic Acute 1 - H400	
Aquatic Chronic 3 - H412	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Get medical attention if any discomfort continues.
Inhalation	Remove person to fresh air and keep comfortable for breathing. If breathing stops, provide artificial respiration. Get medical attention if any discomfort continues.
Ingestion	Do not induce vomiting. Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable seek hospital and bring these instructions.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing. Show this Safety Data Sheet to the medical personnel.
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Get medical attention if any discomfort continues.

987- MASSIVELINE Teak Oil

Protection of first aiders No specific requirements are anticipated under normal conditions of use.

4.2. Most important symptoms and effects, both acute and delayed

General information Not dangerous under normal conditions. Get medical attention if any discomfort continues, and take this SDS with you.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

5.2. Special hazards arising from the substance or mixture

Specific hazards Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m³. Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours. Risk of re-ignition after fire has been extinguished. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapours. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Use special protective clothing. Regular protection may not be safe. Cool containers exposed to flames with water until well after the fire is out. Containers close to fire should be removed or cooled with water. Do not allow water to contact any leaked material. Control run-off water by containing and keeping it out of sewers and watercourses.

Special protective equipment for firefighters Wear chemical protective suit. Use air-supplied respirator, gloves and protective goggles. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Take precautionary measures against static discharges. Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground. Avoid release to the environment. Collect and dispose of spillage as indicated in Section 13.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Avoid contact with skin or inhalation of spillage, dust or vapour. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13. Flush contaminated area with plenty of water. Take care as floors and other surfaces may become slippery.

6.4. Reference to other sections

SECTION 7: Handling and storage

987- MASSIVELINE Teak Oil

7.1. Precautions for safe handling

Usage precautions Do not eat, drink or smoke when using the product. Avoid inhalation of vapours/spray and contact with skin and eyes. Provide adequate ventilation. Persons with impaired lung function should not handle this product..

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep separate from food, feedstuffs, fertilisers and other sensitive material. Avoid contact with oxidising agents. Take precautionary measures against static discharges. Store in tightly-closed, original container in a well-ventilated place. Store between 5 and 25°C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Containers, which are opened should be properly resealed and kept upright to prevent leakage.

Storage class Chemical storage.

7.3. Specific end use(s)

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Protective equipment



Appropriate engineering controls Provide adequate ventilation. Avoid inhalation of vapours.

Eye/face protection Wear tight-fitting, chemical splash goggles or face shield.

Hand protection Use protective gloves.

Other skin and body protection Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures Provide eyewash station. Wash promptly if skin becomes contaminated. Contaminated clothing should be placed in a closed container for disposal or decontamination. Warn cleaning personnel of any hazardous properties of the product. Remove contaminated clothing and wash the skin thoroughly with soap and water after work. When using do not eat, drink or smoke.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.

Colour Colourless.

Odour Solvent.

Odour threshold No information required.

pH Technically not feasible.

Melting point Technically not feasible.

Initial boiling point and range 140 - 220 °C

987- MASSIVELINE Teak Oil

Flash point	38°C CC (Closed cup).
Evaporation rate	No specific test data are available.
Evaporation factor	No specific test data are available.
Flammability (solid, gas)	No specific test data are available.
Upper/lower flammability or explosive limits	LEL : 0,21% volume / UEL : 2,8% volume
Other flammability	No specific test data are available.
Vapour pressure	<200 mmHg at 38°C
Vapour density	No specific test data are available.
Relative density	Technically not feasible.
Bulk density	0,81 - 0,85 g/cm ³ , 25°C'de
Solubility(ies)	Insoluble in water.
Partition coefficient	No specific test data are available.
Auto-ignition temperature	No specific test data are available.
Decomposition Temperature	Technically not feasible.
Viscosity	No specific test data are available.
Explosive properties	Technically not feasible.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	There are no chemical groups present in the product that are associated with oxidising properties.
Comments	Information given is applicable to the product as supplied.

9.2. Other information

Volatile organic compound <700 g/L (Theoretical), Directive 2004/42/CE Annex.II.A-f

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Keep away from oxidizing agents, strongly alkaline and acidic materials to prevent the possibility of exothermic reaction.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Will not polymerise.

10.4. Conditions to avoid

Conditions to avoid Avoid contact with strong oxidising agents. Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or direct sunlight.

10.5. Incompatible materials

Materials to avoid Strong alkalis. Strong acids.

987- MASSIVELINE Teak Oil

10.6. Hazardous decomposition products

Hazardous decomposition products Carbon monoxide (CO). Oxides of carbon. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m³.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No information available.

Other health effects There is no evidence that the product can cause cancer.

Skin corrosion/irritation

Skin corrosion/irritation Repeated exposure may cause skin dryness or cracking.

Serious eye damage/irritation

Serious eye damage/irritation Repeated exposure may cause chronic eye irritation.

Respiratory sensitisation

Respiratory sensitisation Vapour from this chemical can be hazardous when inhaled. Gas or vapour at high concentrations may irritate respiratory system.

Skin sensitisation

Skin sensitisation Repeated exposure may cause skin dryness or cracking.

Specific target organ toxicity - single exposure

STOT - single exposure May cause drowsiness or dizziness.

Target organs Central nervous system

Aspiration hazard

Aspiration hazard May be fatal if swallowed and enters airways.

Toxicological information on ingredients.

2-bütanonoksim

Acute toxicity - dermal

ATE dermal (mg/kg) 1,100.0

3-iodo2-propynyl butyl carbamate

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 1,400.0

Species Rat

ATE oral (mg/kg) 1,400.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,100.0

Species Rabbit

ATE dermal (mg/kg) 2,100.0

Acute toxicity - inhalation

987- MASSIVELINE Teak Oil

Acute toxicity inhalation (LC ₅₀ vapours mg/l)	2.756
Species	Rat
ATE inhalation (vapours mg/l)	2.756

SECTION 12: Ecological Information

12.1. Toxicity

Acute toxicity - fish	LC ₅₀ , 96 hours: Veri yok mg/l, Fish
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: Veri yok. mg/l, Daphnia magna
Acute toxicity - aquatic plants	IC ₅₀ , 72 hours: Veri yok. mg/l, Algae

Ecological information on ingredients.

3-iodo2-propynyl butyl carbamate

Acute aquatic toxicity

LE(C)₅₀ 0.01 < L(E)C50 ≤ 0.1

M factor (Acute) 10

Chronic aquatic toxicity

M factor (Chronic) 1

cobalt bis(2-ethylhexanoate)

Acute aquatic toxicity

LE(C)₅₀ 0.1 < L(E)C50 ≤ 1

M factor (Acute) 1

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient No specific test data are available.

12.4. Mobility in soil

Mobility The product contains substances which are insoluble in water and which may spread on water surfaces.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

987- MASSIVELINE Teak Oil

General information When handling waste, the safety precautions applying to handling of the product should be considered. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Dispose of empty containers in accordance with national regulations. International Disposal Code of product : 080111
International Disposal code of containers : 150110

Disposal methods Burning

Waste class H3-B H-5

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1263

UN No. (IMDG) 1263

UN No. (ICAO) 1263

UN No. (ADN) 1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID) PAINT

Proper shipping name (IMDG) PAINT (CONTAINS hidrokarbonlar, C9-C12, n-alkanlar, iso alkanlar, siklik bileşimler, aromatlar (2-25%), cobalt bis(2-ethylhexanoate))

Proper shipping name (ICAO) PAINT

Proper shipping name (ADN) PAINT

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID classification code F1

ADR/RID label 3

IMDG class 3

ICAO class/division 3

ADN class 3

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ADN packing group III

ICAO packing group III

14.5. Environmental hazards

987- MASSIVELINE Teak Oil

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS	F-E, S-E
ADR transport category	3
Emergency Action Code	•3Y
Hazard Identification Number (ADR/RID)	30
Tunnel restriction code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation	Dangerous Substances Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Directive 91/155/EEC : System of specific information relating to Dangerous Preparations Regulation No: 1907/2006 of the European Parliament and the Council of 01.06.2007 (EC) concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures.
----------------	---

15.2. Chemical safety assessment

SECTION 16: Other information

Revision comments	This is first issue.
Issued by	Elvan Saglam / DYO Architectural Paints R&D Specialist. Certified Safety Data Sheet Preparer, Certification no: GBF-1801 www.dyo.com.tr elvan.saglam@dyo.com.tr Tel : +90 262 754 75 60
Revision date	25/01/2016
Revision	0.1
Supersedes date	25/01/2016
SDS number	20429

987- MASSIVELINE Teak Oil

Hazard statements in full

H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child if swallowed.
H372 Causes damage to organs (Larynx) through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
EUH208 Contains 2-bütanonoksim, 3-iodo2-propynyl butyl carbamate, cobalt bis(2-ethylhexanoate). May produce an allergic reaction.